BILL OF MATERIALS CONCRETE NOTE: 1. REFER TO GENERAL TOLERANCES UNO DESCRIPTION ITEM NO. 2. 3. STEEL AND FIBER REINFORCED CONCRETE - 40MPA CAST PIT 1 ALL LIFTING POINTS TO BE USED WHEN LIFTING 1 MINIMUM STRENGTH OF CONCRETE SHALL BE 2 LOCK BOX 25MPA AT THE TIME OF LIFTING 3 4 5. REFER TO BVCI-INS-C-001 (STD INSTALLATION GUIDE) FOR INSTALLATION DETAILS 4 8 M12x50 FERRULE (ZINC) 6. RÉFER TO ANCON LIFTING ARRANGEMENT PLAN 1600 5 UNISTRUT - P3300 4 1500 1100 CLEAR OPENING 5 2 ROUTE/PIT MARKER CLEAR OPENING LOCATION 900 **PLAN VIEW** ISOMETRIC VIEW SIMILAR AS PER EAST FACE 283 0 0 0 0 R65 **¥**45 **TYPICAL** @170 CRS 1440 206 1090 355 80 TYPICAL WEST FACE SOUTH FACE **EAST FACE NORTH FACE** WALL THICKNESS TOLERANCE NOTES:

1. CONCRETE TOLERANCES TO BE INCONJUCTION / ACCORDANCE WITH AS3600 - CONCRETE STRUCTURES

2. WHEN A BROOME FINISH IS REQUIRED THE GENERAL TOLERANCE SUPERCEEDS THE FLATNESS TOLERANCE

3. WALL THICKNESS - DIMENSION AS NOTED IS MINIMUM THICKNESS ONLY

4. CONCRETE GRADE - 40MPA UNLESS NOTED OTHERWISE

5. DIMENSIONS ARE NOT INCLUSIVE OF SEALANTS OF JOINTS

6. SURFACE FINISH - CLASS 4 (AS3610.1) CHK / APPR CARNGHAM ROAD **CUBIS SYSTEMS AUSTRALIA** BALLARAT, VIC 3351 CATALOGUE PRODUCTS (03) 5335 8741 RPEQ DOCUMENT # Rev DESCRIPTION DATE: BY: ECO#: PIT CONCRETE C1 CLASS D 2 STRADBROKE STREET REVISION CONTROL GENERAL TOLERANCES
NOMINAL: HEATHWOOD, QLD 4110 (07) 3714 0444 FLATNESS: (NOT INCLUDING BROOME FINISH) 1100Kg 1M AND ABOVE DRAWN TO AS 1100
DO NOT SCALE
FROM SHEET UP TO 1000mm CONCRETE 40MPA 50201208-01 THE INFORMATION DISCLOSED IN THIS DOCUMENT IS CONFIDENTIAL AND IS NOT WITHOUT THE EXPRESS CONSENT OF CUBIS SYSTEMS AUSTRALIA TO BE COPIED, REPRODUCED, OR GIVEN TO ANY OTHER PARTY IN ANY FORM AND B ±4mm PER 1M WIDTH 1mm IN 200mm UP TO A MAXIMUM OF 20mm TOLERANCE: IN 1M LENGTH ±5mm 1/1 1:20 2/12/2015 THAT ALL COPYRIGHT, DESIGNS AND PATENTS VEST IN CUBIS SYSTEMS AUS.