







## ISOMETRIC VIEW SCALE\_1:5

P.ADAMS

DATE LAST SAVE

17/06/2022

TOLERANCE NOTES:

1. CONCRETE TOLERANCES TO BE
 INCONJUCTION / ACCORDANCE WITH
 AS3600 - CONCRETE STRUCTURES

2. WHEN A BROOM FINISH IS REQUIRED THE
 GENERAL TOLERANCE SUPERCEDES THE
 FLATNESS TOLERANCE

3. WALL THICKNESS - DIMENSION AS NOTED
 IS MINIMUM THICKNESS ONLY

4. CONCRETE GRADE - 40MPA UNLESS NOTED
 OTHERWISE

CONCRETE GRADE - 40117A ONLESS 110.10
 OTHERWISE
 DIMENSIONS ARE NOT INCLUSIVE OF SEALANTS OF JOINTS
 SURFACE FINISH - CLASS 4 (AS3610.1)

	3								CHK / APPR:
	2								DATE:
	1								
Rev. DESCRIPTION				DATE		BY	APPROVED	RPEQ DOCUMENT #:	
	GENERA	ENERAL TOLERANCES REVIS				SION CONTROL			
	NOMINAL:	UP TO 1000mm	1M AND	ABOVE		FLATNESS: (NOT INCLUDING BROOME FINISH)			WEIGHT: 14.6Kg
	TOLERANCE	±5mm	1mm IN 200 A MAXIMUM		±4mm PER 1M WIDTMA IN 1M LENGTH			FERIAL < NOT SPECIFIED>	

PEQ DOCUMENT #: 14.6Kg

## Infrastructure Products Australia

A CRH COMPANY

1 REEVES COURT BREAKWATER, VIC 3219 HEATHWOOD, QLD 4110 1800 065 356

NBR<u>A</u>DIC ⊕ = ∃ 91 STRADBROKE STREET

		ISSUED FOR CLIENT REVIEW ONLY							
		ISSUE DATE		CLIENT APPROVAL					
		Α	17/06/2022						
	DRAFTED DATE: 17/06/2022	PART/PRODUCT # 50203570		QUOTE #	ORDER #				
١	DRAFTED BY:	REINFORCEMENT COMPUTA	TION	PIT #	ITEM TYPE				

50203570
REINFORCEMENT COMPUTATION CUBIS SYSTEMS/AUSPITS

50203570 1/1 A3 1:10