

TOLERANCE NOTES:

1. CONCRETE TOLERANCES TO BE INCONJUCTION / ACCORDANCE WITH AS3600 - CONCRETE STRUCTURES

2. WHEN A BROOME FINISH IS REQUIRED THE GENERAL TOLERANCE SUPERCEEDS THE FLATNESS TOLERANCE

3. WALL THICKNESS - DIMENSION AS NOTED IS MINIMUM THICKNESS ONLY

4. CONCRETE GRADE - 40MPA UNLESS NOTED OTHERWISE Rev. DESCRIPTION DATE BY APPROVED 16/11/2021 HEATHWOOD, QLD 4110 REVISION CONTROL (07) 3714 0444 **GENERAL TOLERANCES** CABEYSINGH THE INFORMATION DISCLOSED IN FLATNESS: (NOT INCLUDING BROOME FINISH) 243.97Kg A CRH COMPANY

AUSTRALIA TO BE COPIED, REPRODUCED, OR GIVEN TO ANY OTHER PARTY IN ANY FORM AND THAT ALL COPYRIGHT, DESIGNS AND PATENTS VEST IN OTHERWISE
DIMENSIONS ARE NOT INCLUSIVE OF
SEALANTS OF JOINTS
SURFACE FINISH - CLASS 4 (AS3610.1) UP TO 1000mm 1M AND ABOVE 1800 SLEEPER, END MATERIAL ±4mm PER 1M WIDTH 1mm IN 200mm UP TO A MAXIMUM OF 20mm TOLERANCE: IN 1M LENGTH ±5mm 50202451 1 / 1 А3 1:20